


**NOTES:**

- 1. ① to ⑯ see parts list (D15-816-RAET-XXXX-2).
- 2. Customer specified 'U' length.
- 3. Install top and bottom mounted units in horizontal pipe with flow arrow  $\longleftrightarrow$  parallel to flow direction.

Information contained in this document is confidential and proprietary information of Telematic Controls Inc. This document may not be reproduced or distributed for any reason without express written permission of Telematic Controls Inc. All rights of design, invention and copyright are reserved.

APPROVALS		DATE			
DRN	MW	13MAY13			
CHKD	EC	23MAY13			
APP	TDH	03Jun13	TITLE CLASSIC 816 Series <b>Packing Gland - Threaded - 1" MNPT</b> Low Pressure (50 psi) Local Electronics		
All dimensions are shown in inches with cm shown in brackets  TOLERANCES ARE: DECIMALS      ANGLES .X ± 0.1            ±0.5° .XX ± 0.02 .XXX ± 0.007			SIZE A3	DWG NO. D15-816-RAET-XXXX-1	REV 2
SCALE NTS			SHEET 1 OF 2		

Rev	Description	App.	Date
0	Initial release	Chidley	14May98
1	Edited text		26Jan11
2	Changed footer note. Added confidential note. Modified Title box & Rev. Table. Modified notes. Deleted 4 triangle & dim.	TDH	03Jun13

REFERENCE DWGS:
D15-816-RAET-XXXX-2

ITEM	DESCRIPTION	PART NUMBER	QTY
*1	Sensor Assembly; (probe only)	P32-RAETXXXX	1
2	Flameproof Enclosure (1" x 1" FNPT)	N10-100A-E	1
3a	<input checked="" type="checkbox"/> Glass Lens Cover - Flameproof	M10-1G00	1
3b	<input type="checkbox"/> Blind Cover - Flameproof	M10-1B00	1
4	CLASSIC Electronics Module		
	(12 - 24 VDC; 115-230 VAC, 50-60 Hz)	L10-800-C-E	1
5	Nameplate, Foil	2400-0002	1
6	Nameplate, Overlay	2401-0001	1
7	Nut	2510-0305-B	1
8	Hex Cap Screw, 1/4" - 28 x 1/2" SS	2540-0020	1
9	Packing Follower	2510-0307-B	1
10	Seal Follower	2510-0304-B	1
11	Seal (U-Cup)	2510-0440	1
12	Nut w/ Coupling	2510-0306-B	1
13	Stainless Set Screw, 10 - 24 x 3/8" Allen	2540-0021	1
14	Sleeve	2510-0300-B	1
15	1/8" Sq. Teflon	Z2510-0429	A/R
16	Hardware Reducer 1" x 1/2"	2510-0031	1


**NOTES:**

**\*1. Sensor Assembly Selection Guide:**

P32-RAETXXXX where XXXX = desired probe 'U' length.

eg. 6" = P32-RAET0060	36" = P32-RAET0360
12" = P32-RAET0120	48" = P32-RAET0480
18" = P32-RAET0180	60" = P32-RAET0600
24" = P32-RAET0240	

Information contained in this document is confidential and proprietary information of Telematic Controls Inc. This document may not be reproduced or distributed for any reason without express written permission of Telematic Controls Inc. All rights of design, invention and copyright are reserved.

Rev	Description	App.	Date	APPROVALS	DATE		TITLE		REV	
0	Initial release	Garland	12May98	DRN MW	13MAY13		Parts List - CLASSIC 816 Series			D15-816-RAET-XXXX-2
1	Edited text		26Jan11	CHKD EC	23MAY13		Packing Gland - Threaded - 1" MNPT			
2	Changed footer note. Added confidential note. Modified Title box & Rev. Table. Added to item16.	TDH	03Jun13	APP TDH	03JUN13		Low Pressure (50 psi)			
				All dimensions are shown in inches with cm shown in brackets  TOLERANCES ARE: DECIMALS      ANGLES .X ± 0.1            ±0.5° .XX ± 0.02 .XXX ± 0.007		SIZE A3	DWG NO.	SHEET 2 OF 2		
						SCALE NTS				